

construction:

- **SE700:** extruded aluminium and natural tone anodised aluminium with black extruded aluminium deflectors
- **plenum:** galvanised steel sheet, optional insulation.

Specification description

Example:

Aluminium linear diffuser with 3 exhaust slots and adjustable deflectors. Plenum can be supplied mounted or separate, with internal insulation, with circular inlet spigot. Natural to anodised diffuser, black aluminium deflectors

Type: SE713 + SP723 G
L = ... mm

Fixing

- Either by direct and fixed mounting of the diffuser on the plenum (mounting by Grada upon request).
- Plenum provided with mounting eyes (Ø 7 mm), mounting straps available upon request.

How to order

SE713 with 3 slots and black aluminium deflectors

S	E	7	1	3	-	F	1	0	0	0	-	-	-	-
---	---	---	---	---	---	---	---	---	---	---	---	---	---	---

- slot length (mm)
- F: painted in RAL-colors
- : slot diffuser in one piece with end caps on both sides
- number of slots
- 0: exhaust, no deflectors
- 1: supply, with black aluminium deflectors
- 2: supply, with white aluminium deflectors
- E: frame width 25 mm

Slot diffuser in a panel

S	E	7	1	3	P	F	1	2	0	0	1	3	5	0
---	---	---	---	---	---	---	---	---	---	---	---	---	---	---

- slot length (mm) panel length
- F: painted in RAL-colors
- P: with panel, with rebord on all sides*
- Z: with panel, with fine line 5/8 on the two shortest sides**
- number of slots
- 1: black deflectors
- 2: white deflectors

* All panels have a width of 300 mm with rebord on all sides and a flange of 10 mm at all sides

** All panels have a width of 300 mm with rebord on two sides and a flange of 10 mm at the longest side. The length of the panel is the total length, fine line included

remark: the length of the panel must be 55 mm longer than the nominal length of the diffuser.

